



AACT ACRYLIC

Waterborne

Characteristics:

- Very low VOC
- Environmentally friendly
- Meets Federal Specification TTP-1952 B
- Excellent color retention
- Spreading rate of 350 linear feet per gallon of 4-inch line
- Excellent flexibility
- Non-flammable
- Non-bleeding
- Excellent glass bead retention and night visibility
- Easy clean-up with soap and water
- Recommended for athletic field markings

Cautions:

- High humidity will adversely affect drying time
- Keep from freezing
- Addition of water or other soluble solvents will adversely affect dry time
- All equipment should be cleaned before paint dries

Specifications	
Viscosity: 75 to 85 Krebs Units	Total Solids: 50 % minimum
Weight per gallon: 11.00 minimum	Water resistance: 4 hours minimum drying at temperatures above 50 degrees F and humidity below 80% before exposure to moisture
Dry to NPU: 15 to 60 minutes track free at 15 mils wet	
Vehicle Type: 100% Acrylic Emulsion	Shelf Life: 1 year minimum properly stored

Safety Coatings, Inc.

20180 Safety Lane

Post Office Box 399

Foley, AL 36536-0399

Phone: (251) 943-1638

Fax: (251) 943-3689

Website: www.safetycoatings.com

E-mail: info@safetycoatings.com