



ACRYBAR

Durable Fast Dry Waterborne

Characteristics:

- Low VOC
- High Durability and Toughness
- Semi-gloss finish for cleaner line, longer
- Non-flammable
- Non-bleeding
- Excellent glass bead retention including big beads for wet night visibility
- Easy clean-up with soap and water
- Recommended for crosswalks and other high traffic areas
- Latest technology 100% Acrylic Binder

Cautions:

- CANNOT be used in galvanized, brass, aluminum, or steel equipment – Recommend stainless steel or plastic components
- Keep from freezing
- Addition of water or other soluble solvents will adversely affect dry time
- All equipment should be cleaned before paint dries

Specifications	
Viscosity: 75 to 85 Krebs Units	Total Solids: 60 % minimum
Weight per gallon: 11.00 minimum	Water resistance: 2 hours minimum drying at temperatures above 50 degrees F and humidity below 80% before exposure to moisture
Dry to NPU: 3 to 10 minutes track free at 15 mils wet	
Vehicle Type: 100% Acrylic – latest technology resin	Shelf Life: 1 year minimum properly stored

Safety Coatings, Inc.
20180 Safety Lane
Post Office Box 399
Foley, AL 36536-0399

Phone: (251) 943-1638
Fax: (251) 943-3689
Website: www.safetycoatings.com
E-mail: info@safetycoatings.com