



ACRYGLOSS

Cold Applied Semi-gloss Waterborne

Characteristics:

- Low VOC
- Environmentally friendly
- Special formulation for resistance to jet fuels, kerosene, etc.
- Semi-gloss finish for resistance to dirt pick-up
- Spreading rate of 350 linear feet per gallon of 4-inch line
- Non-flammable
- Non-bleeding
- Excellent glass bead retention and night visibility
- Easy clean-up with soap and water
- Recommended for sealcoated surfaces

Cautions:

- Smooth surfaces should be roughened for better bonding
- Keep from freezing
- Addition of water or other soluble solvents will adversely affect dry time
- All equipment should be cleaned before paint dries

Specifications	
Viscosity: 75 to 85 Krebs Units	Total Solids: 65 % minimum
Weight per gallon: 12.00 minimum	Water resistance: 3 hours minimum drying at temperatures above 50 degrees F and humidity below 80% before exposure to moisture
Dry to NPU: 5 to 15 minutes track free at 15 mils wet	Shelf Life: 1 year minimum properly stored
Vehicle Type: 100% Hard Acrylic Binder	

Safety Coatings, Inc.

20180 Safety Lane

Post Office Box 399

Foley, AL 36536-0399

Phone: (251) 943-1638

Fax: (251) 943-3689

Website: www.safetycoatings.com

E-mail: info@safetycoatings.com