



ACRYLINE

Cold Applied Fast Dry Waterborne

Characteristics:

- Low VOC
- Environmentally friendly
- Excellent color retention
- Spreading rate of 350 linear feet per gallon of 4-inch line
- Non-flammable
- Non-bleeding
- Excellent glass bead retention and night visibility
- Easy clean-up with soap and water
- Recommended for sealcoated surfaces

Cautions:

- Smooth surfaces should be roughened for better bonding
- Keep from freezing
- Addition of water or other soluble solvents will adversely affect dry time
- All equipment should be cleaned before paint dries

| Specifications | |
|---|--|
| Viscosity: 75 to 85 Krebs Units | Total Solids: 70 % minimum |
| Weight per gallon: 13.50 minimum | Water resistance: 3 hours minimum drying at temperatures above 50 degrees F and humidity below 80% before exposure to moisture |
| Dry to NPU: 5 to 15 minutes track free at 15 mils wet | Shelf Life: 1 year minimum properly stored |
| Vehicle Type: 100% Acrylic Binder | |

Safety Coatings, Inc.

20180 Safety Lane

Post Office Box 399

Foley, AL 36536-0399

Phone: (251) 943-1638

Fax: (251) 943-3689

Website: www.safetycoatings.com

E-mail: info@safetycoatings.com