



# ACRYSET

Cold Applied Durable Fast Dry Waterborne

## Characteristics:

- Low VOC
- Excellent glass bead retention and night visibility
- Dry through in 2 hours maximum even at high humidity
- Non-flammable
- Non-bleeding
- Spreading rate of 350 linear feet per gallon of 4-inch line
- Easy clean-up with soap and water
- Recommended for sealcoated surfaces
- 100% Acrylic Binder

## Cautions:

- CANNOT be used in galvanized, brass, aluminum, or steel equipment – Recommend stainless steel or plastic components
- Keep from freezing
- Addition of water or other soluble solvents will adversely affect dry time
- All equipment should be cleaned before paint dries

Specifications	
Viscosity: 80 to 90 Krebs Units	Total Solids: 70 % minimum
Weight per gallon: 13.50 minimum	Water resistance: 2 hours minimum drying at temperatures above 50 degrees F and humidity below 80% before exposure to moisture
Dry to NPU: 3 to 10 minutes track free at 15 mils wet	Shelf Life: 1 year minimum properly stored
Vehicle Type: 100% Acrylic fast release resin	

**Safety Coatings, Inc.**

20180 Safety Lane

Post Office Box 399

Foley, AL 36536-0399

Phone: (251) 943-1638

Fax: (251) 943-3689

Website: [www.safetycoatings.com](http://www.safetycoatings.com)

E-mail: [info@safetycoatings.com](mailto:info@safetycoatings.com)