



# Hi Build

## Durable Waterborne Traffic Paint

### Characteristics:

- Low VOC
- Excellent initial and long term retroreflectivity (works best with big beads)
- Can be applied with standard waterborne striping equipment with no modifications
- Can be used to refurbish existing thermoplastic lines
- Lower cost than other durable products
- Excellent for crosswalks and legend markings
- Can be applied at films up to 30 mils wet without cracking
- 2 to 3 years durability
- Spreading rate of 180 to 200 linear feet per gallon of 4-inch line

### Cautions:

- CANNOT be used in galvanized, brass, aluminum, or steel equipment -
- Recommend stainless steel or plastic components
- Keep from freezing
- Addition of water or other soluble solvents will adversely affect dry time
- All equipment should be cleaned before paint dries

Specifications	
Viscosity: 85 to 95 Krebs Units	Total Solids: 75 % minimum
Weight per gallon: 13.0 minimum	Volume Solids: 60 % minimum
Dry to NPU: 3 to 10 minutes track free at 25-30 mils wet	Shelf Life: 1 year minimum properly stored
Vehicle Type: Patented crosslinking technology acrylic binder	

**Safety Coatings, Inc.**  
20180 Safety Lane  
Post Office Box 399  
Foley, AL 36536-0399

Phone: (251) 943-1638  
Fax: (251) 943-3689  
Website: [www.safetycoatings.com](http://www.safetycoatings.com)  
E-mail: [info@safetycoatings.com](mailto:info@safetycoatings.com)