



LOOP GUARD FOUR

ONE COMPONENT POLYMER LOOP SEALANT

Characteristics:

- One component
- Easy clean-up with soap and water
- Fully encapsulates the loop
- Non-flammable – safe to use
- Very flexible and good adhesion to pavement
- Meets California environmental requirements
- No strong odors
- Pleasant gray color
- WILL NOT ATTACK ASPHALT

Application:

- Easily pumped from 5 gallon cans (4.5 gallons per pail)
- Easily poured from handy 1 gallon squeeze bottles – 4 per case
- Easily applied from quart tubes – 12 per case (29 oz. Per tube)
- Cover with sand immediately after application

Cautions:

- Keep from freezing

Specifications	
Color: Medium gray	Elongation: 200-400%
Viscosity: Approximately 120-140 Krebs Units (30,000- 50,000 cps)	Shelf Life: Guaranteed 1 year (typically 2+ years)
Weight per gallon: 12.0 minimum	Tensile Strength: 180-400 psi
Tack free time: 30 minutes maximum	

Safety Coatings, Inc.

20180 Safety Lane

Post Office Box 399

Foley, AL 36536-0399

Phone: (251) 943-1638

Fax: (251) 943-3689

Website: www.safetycoatings.com

E-mail: info@safetycoatings.com