



# PLASTIBAR

## Thermoplastic Paint

### Characteristics:

- Up to 5 times the life of regular traffic paint
- Excellent proven substitute for hot and pre-formed thermoplastic
- Hard semi-gloss finish, stays cleaner, longer
- Outstanding durability
- Spreading rate of 350 linear feet per gallon of 4-inch line
- Can be applied with standard striping equipment, without modification
- Particularly recommended for high wear traffic areas, such as intersections, crosswalks, legends, factories, and warehouses
- Excellent hiding and brightness
- Superior bead adhesion for high night visibility
- Easy clean-up with Xylene or Toluene

### Cautions:

- May bleed on fresh asphalt or sealcoated surfaces – See “Application Procedures”
- This paint may lift improperly aged or inferior asphalt pavements
- Keep away from all heat sources – Flammable

Specifications	
Viscosity: 75 to 85 Krebs Units	Total Solids: 68 % minimum
Weight per gallon: 11.50 minimum	Solvent Type: Toluene
Dry to NPU: 2 to 10 minutes track free at 15 mils wet	Shelf Life: 1 year minimum properly stored
Vehicle Type: Thermoplastic polymer	

**Safety Coatings, Inc.**

20180 Safety Lane

Post Office Box 399

Foley, AL 36536-0399

Phone: (251) 943-1638

Fax: (251) 943-3689

Website: [www.safetycoatings.com](http://www.safetycoatings.com)

E-mail: [info@safetycoatings.com](mailto:info@safetycoatings.com)